

# TeraStation Pro™8

TS-8VHL/R6 Series

## **Eight-Drive Business Class Reliable NAS**



Buffalo's TeraStation Pro™ 8 is an eight-drive high performance network storage solution ideal for businesses and demanding users looking to implement a RAID based network storage solution for larger networks and business critical applications. With the powerful Intel® Atom™ D510 Dual-Core Processor, TeraStation Pro 8 provides exceptional performance during file transfers and everyday NAS functions. TeraStation Pro 8 runs many services simultaneously and the Dual-Core processor enables the ability to focus on multiple tasks simultaneously with minimal performance degradation: experience maximum network throughput while a replication job runs in the background or perform fast search indexing. TeraStation Pro 8 is packed with business class features such as Active Directory support, quota support, share level Replication, Failover support, dual gigabit Ethernet ports, hot-swap hard drives and USB 2.0 accessory support.

# NovaBackup® Business Essentials



#### **High Speed NAS (Read)**

TeraStation Pro\*

108 MB/s

TeraStation || 69 MB/s

TeraStation ES 49 MB/s

\*Preformance is estimated

PC: Dell Vostro 200 | CPU: Intel Core2Duo E6750 (2.66GHz) Mem: 3 GB | NIC: Intel PRO1000/PT OS: Windows XP Professional Service Pack 2 Software: Iometer | RAID 5, Sequential read (RAID 1 for TeraStation Pro Duo)

\*TeraStation Pro units tested include TeraStation Pro Duo (RAID 1), TeraStation Pro Quad (RAID 5), TeraStation Pro Rackmount (RAID 5), TeraStation Pro 6 WSS (RAID 5) and TeraStation Pro 8 WSS (RAID 5)


#### **Features and Benefits**

- Intel® Atom™ 1.66 GHz Dual Core / 2 GB RAM
- Powerful hardware makes data transfer faster. Multiple PCs access is also faster
- Eight front loading hot swap hard drives with lockable front panel
- Active Directory support
- Quota support prevents users/groups from consuming too much disk space
- Scheduled shut down reduces energy costs
- DFS (Distributed File System) support
- Easy setup wizard and management through intuitive web interface
- Cartridge mounted hot swap hard drives behind the front panel for easy drive access and replacement
- 1000/100/10 Gigabit Ethernet with Jumbo Frame
- Two Ethernet ports for port trunking
- Supported RAID levels: 0, 1, 5, 6, 10, 50, 51, 60, 61 Normal (JBOD)
- Share level replication feature synchronizes files of TeraStations


- Failover synchronizes configuration data and files between two TeraStation PROs. When the main TeraStation fails, the backup TeraStation automatically becomes a main TeraStation
- Hot spare enables automatic RAID build in case of a drive failure
- Optional AES-128 bit hard drive encryption
- Large silent fan and advanced ventilation design cool down hard drives and other components efficiently
- LCD Display shows important TeraStation information and disk status
- Built-in FTP server functionality
- BitTorrent Client: Download digital content from the Internet directly to your TeraStation
- DLNA CERTIFIED built-in media server for streaming multimedia content
- 2 USB 2.0 ports for external drive, printer and UPS connectivity
- 10 licenses of NovaBACKUP® Business Essentials Backup software included. Backup Included: Back up up to 10 Windows PCs, Windows Servers, Exchange or MS SQL databases
- 3-Year Limited Warranty

## **RAID Support for Maximum Flexibility and Reliability**

# RAID 0 Striping Mode




RAID 1
Mirroring Mode



RAID 5
Parity Mode



RAID 6
Double Parity Mode





# TeraStation Pro™8

TS-8VHL/R6 Series

## TS-8VH24TL/R6(24TB), TS-8VH16TL/R6(16TB), TS-8VH8.0TL/R6(8TB), TS-8VHL/E(Enclosure Model)



#### **SPECIFICATIONS**

Hardware Specification

Intel Atom D510 1.66GHz (Dual Core) Processor

Memory DDR2-800 2GB

**Ethernet Port** 

IEEE802.3ab / IEEE802.3u / IEEE802.3 Interface

(1000BASE-T / 100BASE-TX / 10BASE-T)

Data Transfer Rate 1000Mbps full-duplex

100Mbps half-duplex/full-duplex 10Mbps half-duplex/full-duplex

Number of Ports 2 ports (AUTO-MDIX)

Connector Type RJ-45 8pin Transmission Distance 100m TCP, UDP Protocol Network File Protocol SMB/CIFS

AFP HTTP, HTTPS FTP, FTPS, SFTP

NFS

USB Port (\* It cannot be used to connect to a computer)

Interface 2.0/1.1 interface Number of Ports USB 2.0/1.1: 2 ports (Type A)

**UPS Port** 

UPS port (D-sub 9pin (Male)) x 1 port Interface

LCD

**Backlight Color** Normal operation: Blue

Error: Red

[Firmware version][Host name/IP address], Contents

[Date/Time], [Link Speed], Error Message,

and Information Message

Internal HDD (SATA II)

SerialATA II (rev. 2.0) Interface Number of Ports 8 ports (8HDDs are installed) Data Transfer Rate Max 3.0Gbps (Theoretical)

Fan

92mm x 92mm double ball bearing fan x 2 Specification

Size/Weight

W300 x H215 x D230mm Unit Size 12.5kg Unit Weight Package Size W420 x H350 x D350mm

Package Weight 13.5ka **Attachments** 

Power Cable

**Ethernet Cable** 2m category5e straight cable Front panel key x 2

Warranty Statement

Utility CD

Tera Navigator, NAS Navigator2, Turbo PC, Turbo Copy, NovaBACKUP Business Essentials (10 licenses), Quick Setup Guide, User's Manual,

Adobe Reader

Others

Power Input Internal, AC 110-240V 50/60Hz Power Consumption Avg: 120W, Max: 170W Avg: 127VA, Max: 179VA **Heat Generation** Avg: 432kJ/h, Max: 612kJ/h Operation Condition Temperture: 5-35°C,

Humidity: 20-80% (non condensing) VCCI Class A, RoHS, DLNA Standards

Warranty Period 3 years

**OS Support** 

Windows computer with Ethernet interface Machine

Apple Mac series

\*Connect to a computer via Ethernet Client OS Support

[TeraStation]

Windows 7 (32bit/64bit) / Vista (32bit/64bit) /

XP (32bit/64bit)\*1 / 2000

Windows Server 2008 R2 / 2008 / 2003 R2 /

2003, Windows 2000 Server MacOS X 10.3.9 or later \*1: Including MCE2005 / MCE2004

Software OS Support

	Windows							Mac OS
	7	Vista	XP*1	2000	Server 2008 R2 /2008	Server 2003 R2 /2003	2000 Server	X 10.3.9 or later 10.4 10.5 10.6
	32bit /64bit	32bit /64bit	32bit /64bit		32bit /64bit	32bit /64bit		
NAS Navigator2	111	V/V	1	1	<b>✓</b>	<b>✓</b>	1	1
NovaBACKUP Business Essentials	V/V	<b>V</b>   <b>V</b>	1	-	~	~	-	-
Turbo PC	1/1	1/1	1	1	-	-	-	-
Turbo Copy	<b>V</b>   <b>V</b>	<b>V</b>   <b>V</b>	1	1	-	-	-	-

√ : supported, - : not supported

Windows: Internet Explorer (6.0 SP2 or later), Browser

FireFox (1.5 or later)

Mac: Safari (2.0 or later), FireFox (1.5 or later)

### About BUFFALO Inc.

#### www.buffalo-asia.com

BUFFALO Inc., based in Nagoya, Japan, is a leading global provider of award-winning networking, storage and multimedia solutions for the home and small business environments as well as for system builders and integrators. With three decades of networking and computer peripheral experience, BUFFALO has proven its commitment to delivering innovative, best-of-breed solutions that have put the company at the forefront of infrastructure technology.

©2011 BUFFALO INC. BUFFALO and BUFFALO logo are either trademarks or registered trademarks of MELCO HOLDINGS INC. TeraStation and TeraStation logo are either trademarks or registered trademarks of BUFFALO INC. or its affliates in the United State and other countries. Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries. The names and logos of other companies mentioned herein belong to their respective owners.

<sup>\*</sup>Data rate, features and performance may vary based on the configuration of your system and other factors,

<sup>1</sup> TB= 1,000,000,000,000 Bytes. Actual data throughput and range will vary depending upon network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead